

AMENDMENT(S) TO THE CLAIMS

1. (Previously Presented) A shooting device, comprising:

at least one of a barrel, a rail and a stock; and

a clampable bipod including a clamp which is releasably clamped to at least one of said barrel, said rail and said stock, and a first leg and a second leg connected to said clamp, said
5 clamp including a plurality of jaws, and a fulcrum between said plurality of jaws and both said first leg and said second leg, said clamp including a first arm connected to said first leg and a second arm connected to said second leg, said first arm including a first cam surface and said second arm including a second cam surface, said fulcrum being provided by said first cam surface in contact with said second cam surface.

2. (Original) The shooting device of claim 1, further including an adjustable compression device connected to said clamp.

3. (Canceled)

4. (Canceled)

5. (Currently Amended) The A shooting device of claim 1, comprising:

at least one of a barrel, a rail and a stock; and

a clampable bipod including a clamp which is releasably clamped to at least one of said barrel, said rail and said stock, and a first leg and a second leg connected to said clamp, said
5 clamp including a plurality of jaws, and a fulcrum between said plurality of jaws and both said

first leg and said second leg, said clamp including a first arm connected to said first leg and a
second arm connected to said second leg, said first arm including a first cam surface and said
second arm including a second cam surface, said fulcrum being provided by said first cam
surface in contact with said second cam surface, wherein each of said first leg and said second
10 leg include a receiver connected to said clamp and an extender connect to said receiver, said
receiver includes a longitudinal direction and a plurality of holes extending in said longitudinal
direction, said extender includes a spring ball received in any of said plurality of holes.

6. (Previously Presented) A clampable bipod for use with a shooting device, comprising:
a first leg and a second leg; and

a clamp connected to said first leg and said second leg, said clamp including a plurality of
jaws, and a fulcrum between said plurality of jaws and both said first leg and said second leg,
5 said clamp including a first arm connected to said first leg and a second arm connected to said
second leg, said first arm including a first cam surface and said second arm including a second
cam surface, said fulcrum being provided by said first cam surface in contact with said second
cam surface.

7. (Original) The clampable bipod of claim 6, further including an adjustable
compression device connected to said clamp.

8. (Canceled)

9. (Canceled)

10. (Currently Amended) ~~The~~ A clampable bipod of claim 6, for use with a shooting device, comprising:

a first leg and a second leg, wherein each of said first leg and said second leg include including a receiver connected to said clamp and an extender connect to said receiver, said
 5 receiver includes including a longitudinal direction and a plurality of holes extending in said longitudinal direction, said extender includes including a spring ball received in any of said plurality of holes; and

a clamp connected to said first leg and said second leg, said clamp including a plurality of jaws, and a fulcrum between said plurality of jaws and both said first leg and said second leg,
 10 said clamp including a first arm connected to said first leg and a second arm connected to said second leg, said first arm including a first cam surface and said second arm including a second cam surface, said fulcrum being provided by said first cam surface in contact with said second cam surface.

11. (Currently Amended) ~~The~~ A clampable bipod of claim 6, for use with a shooting device, comprising:

a first leg and a second leg, wherein each of said first leg and said second leg include including a receiver, an extender received within said receiver, a collet connected to at least one
 5 of said extender and said receiver, and a collet nut connected to said collet; and

a clamp connected to said first leg and said second leg, said clamp including a plurality of jaws, and a fulcrum between said plurality of jaws and both said first leg and said second leg,
said clamp including a first arm connected to said first leg and a second arm connected to said

second leg, said first arm including a first cam surface and said second arm including a second
10 cam surface, said fulcrum being provided by said first cam surface in contact with said second
cam surface.

12. (Currently Amended) ~~The A~~ clampable bipod of claim 6, for use with a shooting
device, comprising:

a first leg and a second leg; and

a clamp connected to said first leg and said second leg, said clamp including a plurality of
5 jaws, and a fulcrum between said plurality of jaws and both said first leg and said second leg,
said clamp including a first arm connected to said first leg and a second arm connected to said
second leg, said first arm including a first cam surface and said second arm including a second
cam surface, said fulcrum being provided by said first cam surface in contact with said second
cam surface, further including an aperture in said clamp, said aperture including a longitudinal
10 direction, at least one of said first leg and said second leg are rotatable about an axis transverse
to said longitudinal direction.

13. (Original) The clampable bipod of claim 12, wherein said clamp includes at least
one leg stop limiting a rotation of at least one of said first leg and said second leg.

14. (Original) The clampable bipod of claim 6, wherein said clamp includes a
cushioning device.

15. (Previously Presented) A method of attaching a clampable bipod to a shooting

device, comprising the steps of:

positioning said clampable bipod adjacent to at least one of a barrel, a rail and a stock of said shooting device;

5 clamping said clampable bipod to at least one of said barrel, said rail and said stock, said clampable bipod including a clamp connected to both a first leg and a second leg said clamp, said clamp including a plurality of jaws, and a fulcrum between said plurality of jaws and both said first leg and said second leg, said clamp including a first arm connected to said first leg and a second arm connected to said second leg, said first arm including a first cam surface and said
10 second arm including a second cam surface, said fulcrum being provided by said first cam surface in contact with said second cam surface.

16. (Currently Amended) The method of claim 15, further including ~~the~~ a step of compressing said clamp on said at least one of a barrel, a rail and a stock using an adjustable compression device connected to said clamp.

17. (Currently Amended) ~~The~~ A method of claim 15, attaching a clampable bipod to a shooting device, comprising the steps of:

positioning said clampable bipod adjacent to at least one of a barrel, a rail and a stock of said shooting device;

5 clamping said clampable bipod to at least one of said barrel, said rail and said stock, said clampable bipod including a clamp connected to both a first leg and a second leg said clamp, said clamp including a plurality of jaws, and a fulcrum between said plurality of jaws and both said first leg and said second leg, said clamp including a first arm connected to said first leg and a

second arm connected to said second leg, said first arm including a first cam surface and said

10 second arm including a second cam surface, said fulcrum being provided by said first cam
surface in contact with said second cam surface; and

~~further including the step of~~ rotating at least one of said first leg and said second leg about
an axis transverse to a longitudinal axis of said clamp.

18. (Currently Amended) The method of claim 15, further including ~~the~~ a step of
extending at least one of said first leg and said second leg.

19. (Currently Amended) The method of claim 15, further including ~~the~~ a step of
pivoting at least one of said first leg and said second leg about said fulcrum of said clamp.

20. (Previously Presented) A shooting device, comprising:

5 at least one of a barrel, a rail and a stock; and

a clampable bipod including:

a first leg and a second leg;

a clamp which is releasably clamped to at least one of said barrel, said rail and said
stock, said clamp being connected to said first leg and said second leg, said clamp including both

10 a plurality of jaws, and a fulcrum between said plurality of jaws and both said first leg and said
second leg; and

an adjustable compression device connected to said clamp, said adjustable
compression device interposed between said plurality of jaws and said fulcrum.

15 21. (Previously Presented) A clampable bipod for use with a shooting device,
comprising:

 a first leg and a second leg;

 a clamp being connected to said first leg and said second leg, said clamp including both a
plurality of jaws, and a fulcrum between said plurality of jaws and both said first leg and said

20 second leg; and

 an adjustable compression device connected to said clamp, said adjustable compression
device interposed between said plurality of jaws and said fulcrum.